

## Product Presentation



## Application

To determine rectangular bending test of rubber products, shoe soles, PU, PVC, TPR foam and other materials. And inspect its degree of damage, cracking and reduced decline by continuously stretch and bending.



## Feature

- Body paint baking processed, easy for maintenance
- Fixture in aluminum material and surface processed with oxidation
- Equip with digital counter, automatically stop after test finished
- The Chamber can meet test requirements with different temperature

## Control system

Control Mode	LCD display
--------------	-------------

## Key Specification

Model	GT-KB05B
Fixture	6 sets, can test 12pcs samples
Bending angle	90±2°
Bending speed	0~110 cam (adjustable)
Winding shaft radius	5± 0.3mm
Specimen dimension	152 * 25mm
Counter	LCD, 0~99,999,999
Control system	Programmable Microprocessor Control
Temperature range	-30~100℃
Power supply	1 φ AC220V 50/60HZ
Dimension(W×D×H)	100X146X104cm
Weight (Approx)	200 kg

## Standards

ASTM D1052, SATRA TM60, BS5131 : 2.1,  
GB 20265 section 4.2, ISO 5423, ISO4643  
HG/T2411

## Accessories

Standard accessories	1pc	Chisel cutter (2mm)
	1pc	Power line